TECH BULLETIN



Nailbase No. 4001

Subject: Foam-Control Nailbase - Fastening Requirements for Sloped Roofs

Date: March 2008 (Revised Jan. 2010)

Minimum fastening requirements for Foam-Control Nailbase have been calculated in accordance with ASCE 7-05 Method 2, Exposure C, Importance factor of 1.0, a maximum roof height of 60 ft. For projects with snow loads and wind speeds in excess of 110 mph, consult a professional engineer for fastening requirements.

Field of Roof


Number of Fasteners for 4' x 8' (1.2m x 2.4m) Nailbase										
Total Load	Roof Slope									
(Snow Load + Dead Load)	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
30 psf	8	8	8	8	8	8	8	8	8	8
40 psf	8	8	8	8	8	8	8	8	12	12
50 psf	8	8	8	8	12	12	12	12	12	12
60 psf	8	8	8	12	12	12	12	12	12	12
70 psf	8	8	12	12	12	12	16	16	16	16
80 psf	8	12	12	12	16	16	16	16	16	16
90 psf	8	16	16	16	16	16	16	16	16	16


Perimeter of Roof

Number of Fasteners for 4' x 8' (1.2m x 2.4m) Nailbase										
Total Load	Roof Slope									
(Snow Load + Dead Load)	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
30 psf	16	16	16	16	8	8	8	8	8	8
40 psf	16	16	16	16	8	8	8	8	12	12
50 psf	16	16	16	16	12	12	12	12	12	12
60 psf	16	16	16	16	12	12	12	12	12	12
70 psf	16	16	16	16	12	12	16	16	16	16
80 psf	16	16	16	16	16	16	16	16	16	16
90 psf	16	16	16	16	16	16	16	16	16	16

The values in the tables are applicable to R-Control Wood Screws when installed into a SPF or equal wood deck (min. 1" pentration) and to R-Control Metal Deck Screws when installed into a steel deck (22 min. gauge).


Fastening Patterns for 4' x 8' Nailbase






8 Fasteners/Bd.


12 Fasteners/Bd.





16 Fasteners/Bd.

24 Fasteners/Bd.







Foam-Control EPS products are manufactured by AFM Corporation licensees.

Copyright ©2010 AFM Corporation.
All rights reserved. Printed in USA.
Foam-Control, Perform Guard, and
Control, Not Compromise are trademarks of
AFM Corporation, Lakeville, MN.



